CCM-215 Self Propelled Passenger Stair





Commercial Chassis Mounted Passenger Aircraft Stair

A high quality passenger stair mounted on commercial chassis to the customers specific requirements. With a height range of 2.4m – 5.8m, the CCM-215 range is suitable for all aircraft from MD80 up to B747 and A340.

- Exceptionally reliable with low long term cost of ownership.
- Extra wide stair and top platform options.
- Mounted on standard commercial
 7. 5 tonne GVW chassis.
- Efficient, stable, safe and effective.
- Ideal smooth action telescopic stair section promotes passenger confidence and security.
- Multiple chassis choices available to suit customer requirements.
- Range of diesel engine options conforming to latest European emission standards.
- Includes all benefits of standard commercial chassis including: automatic transmission; power steering; ABS braking; Air Conditioning.

- Standard stair features include: heavy duty hydraulic stabilisers; automatic stair locking pawls; stair lighting; emergency hand pump, spring loaded self aligning top platform nose section with sliding wing panels.
- Ergonomically designed stair controls fitted within the operators' cab.
- Corrosion resistant features including stainless steel stair elevation running gear.
- Shot blasted and finish painted to customers individual livery requirements with full wax treatment.
- Overhead or totally enclosed Plexi glass canopy options available.
- Can also be supplied fitted to standard AMSS chassis.
- The perfect vehicle which will reliably perform worldwide irrespective of temperature or conditions.
- Complies with Motor Vehicle Construction and Use, Health and Safety, IATA and CEN Standards.



Passenger Stairs

Belt Loaders
Cargo & Freight Vehicles
Toilet & Water Trucks
Aircraft Loaders
Fuel Tank Repair Trolleys
Heater Trolley
Air Conditioning Trolley
Maintenance Docks & Stagings
Special Projects

Remember, each piece of equipment is maintained via our through-life support and training services — wherever you are in the world, 365 days of the year.

+44 (0)1656 743700

. office@dmss.co

W www.amss.co



CCM-215 Self Propelled Passenger Stair



Stair dimensions

- Nominal tread depth 276mm (11")
- Nominal tread width 1,380mm (54") (lower section)
- Nominal tread width 1,600mm (63") (upper section)
- Top Platform width 3,080mm (121")
- Intermediate landing 872mm (34") depth
- Constant riser 196mm (8")

Height range

Low Position 2,450mm (96")High Position 5,750mm (226")

Shipping dimensions

Length 7,190mm (283")Width 3,240mm (127")Height 3,700mm (146")

Shipping weight

• Approx 7,100kg (15,620lb)

Standard features

- Heavy duty hydraulic stabilisers
- Automatic stair locking pawls
- Spring loaded self aligning top platform nose section
- Lockable sliding wing panels
- Emergency hand pump

Options

- Chassis to suit customers requirements
- Extra wide stair section and top platform
- Aircraft movement warning system
- Powered extending top platform
- Fully enclosed canopy with 'air-bridge' style weatherproof bellows



